

**HTS Series 9r Garage Light**  
**Energy Efficient LED Lighting**  
**175-320Watt replacement**

**FEATURED HIGHLIGHTS**

- \*Unlimited application possibilities due to retrofitting
- \*Saves up to 79% of energy consumption
- \*100,000 hour lifespan 5yr. Manufacturers registered warranty
- \*Return on Investment between 18 to 40 months.

**ENVIRONMENTAL FEATURES**

- \*Contains no mercury or lead
- \*Does not produce UV rays
- \*Does not attract insects
- \*Directional light means no light pollution

**ELECTRICAL SPECIFICATIONS**

- \*47 to 63 Hertz ac line power voltage from 90 VAC RMS to 277 VAC RMS
- \*Available to 480 VAC
- \*Nominal operating efficiency is 85% typical at 230 VAC and maximum load
- \*Driver provides surge protection at 305 VAC
- \*Power distributed to onboard drivers per seven LED lights

**SPECIFICATIONS**

- \*\*UL and CUL rated #E326977
- \*\*MADE IN THE U.S.A

The HTS 9r Garage light was specifically designed for low indoor parking garages where a wider spread of light is required. Its superior heat management and compact design make it ideal, 10+ years of maintenance free service.

**OUTPUT SPECIFICATIONS**


*High brightness LED	28
*Number of Lights	59-68watts
*Source power	70
*CRI	5066-5832 at 100%
*Lumens	81.85 LM/W
*Efficacy	5000K
*Chromaticity: White Light	<60°C
*Junction Temperature	LM79 & LM80
*IESNA Tested	-40°C to 70°C
*Operating Range	180
*Nominal Lumens per watt	


**ASSEMBLY**


- \*Metal Core Board
- \*One piece aluminum heat sink dissipates heat
- \*Vibration resistant
- \*ASTM and NEMA Tested


**APPLICATIONS**


- \*Parking Garages
- \*Exterior
- \*Safety
- \*Security

 — HTS-9r28-5 - 59W LED  
 HTS-9r28-7 - 68W LED  
 Lamp Wattage

 — 120 -277, 90 - 305,  
 Voltage

 — 3000K  
 4000K  
 5000K  
 6000K  
 Color Temp

 — 70-120V Step up  
 480v Step Down  
 Power Supply

 — Brown  
 \*White  
 (\*extra cost)  
 Color options

