

HTS Series Garage Light
Energy Efficient LED Lighting
70-320 Watt Replacement

FEATURED HIGHLIGHTS

- *Unlimited application possibilities due to retrofitting
- *Saves up to 79% of energy consumption
- *100,000 hour lifespan 5yr. Manufacturers registered warranty
- *Return on Investment between 18 to 40 months.

ENVIRONMENTAL FEATURES

- *Contains no mercury or lead
- *Does not produce UV rays
- *Does not attract insects
- *Directional light means no light pollution

ELECTRICAL SPECIFICATIONS

- *47 to 63 Hertz ac line power voltage from 90 VAC RMS to 277 VAC RMS
- *Available to 480 VAC
- *Nominal operating efficiency is 85% typical at 230 VAC and maximum load
- *Driver provides surge protection at 305 VAC
- *Power distributed to onboard drivers per seven LED lights

SPECIFICATIONS

- **UL and CUL rated #E326977
- **MADE IN THE U.S.A

The HTS Garage light series was specifically designed for low indoor parking garages where a wider spread of light is required. Its superior heat management and compact design make it ideal, 10+ years of maintenance free service.

OUTPUT SPECIFICATIONS

- *High Brightness LEDs
- *Number of Lights **14-28**
- *Source power **32-68 watts**
- *CRI **74**
- *Lumens **2533-9523 at 100%**
- *Efficacy **76.2 LM/W**
- *Chromaticity: White Light **5000K**
- *Junction Temperature **<60°C**
- *IESNA Tested **LM79 & LM80**
- *Operating Range **-40°C to 70°C**
- *Nominal Lumens per watt **180**

ASSEMBLY

- *Metal Core Board
- *One piece aluminum heat sink dissipates heat
- *Vibration resistant
- *ASTM and NEMA Tested

APPLICATIONS

- *Parking Garages
- *Exterior
- *Safety
- *Security

Dimensions

Weight: (with power supply) 9ar -12 lbs

12" x12" x 9"



	HTS 9ar14-5 32W
	HTS 9ar14-7 34W
	HTS 9r28-5 59W
	HTS 9r28-7 64W

Lamp Wattage

	120 -277, 90 - 305,
--	---------------------

Voltage

	3000K
	4000K
	5000K
	6000K

Color Temp

	70-120V Step up
	480v Step Down

Power Supply

	Brown
	*White (extra cost)

Color options

